AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings of claims in the application.

(Currently Amended) A method of attaching a load carrier fixing member to a

LISTING OF CLAIMS:

1.

vehicle, the method comprising applying adhesive to at least one of a roof of the vehicle roof and/or or the fixing member, and attaching the fixing member to the vehicle, for subsequent attachment of a load carrier to the fixing member, the fixing member comprising a surface for adhering to the

vehicle, characterized in that the surface for adhering to the vehicle comprises at least one undercut

or and/or dovetail.

- 2. (Cancelled)
- 3. (Original) A method as claimed in claim 1, wherein the surface for adhering to the vehicle is indented.
 - (Cancelled) 4.
- 5. (Previously Presented) A method as claimed in claim 1, wherein a load carrier for attaching to the load carrier fixing member is a roof rail or roof rack.
- (Original) A method as claimed in claim 5, wherein the load carrier is a roof rack 6. and the load carrier fixing member is a roof rail.

7. (Previously Presented) A method as claimed in claim 1, wherein the load carrier is attached directly to one or more fixing members.

- 8. (Previously Presented) A method as claimed in claim 1, wherein a fixing member trim finisher is attached to a non adhered side of the fixing member.
- 9. (Original) A method as claimed in claim 8, wherein the fixing member trim finisher is removably attached to the fixing member.
- 10. (Previously Presented) A method as claimed in claim 1, wherein the fixing member comprises at least one gap hider.
- 11. (Currently Amended) A method as claimed in claim 10 [[8]], wherein the at least one gap hider is positioned between the fixing member and the vehicle body roof.
- 12. (Currently Amended) A method as claimed in claim 1, wherein the method further comprises pre-treating the vehicle, the pre-treating including at least one of cleaning a part of the vehicle to be worked on, and/or the use of or using an abrasive material.
- 13. (Currently Amended) A method as claimed in claim 1, wherein the fixing member is secured in position using one or more locating members, which is/are the one or more locating members being shaped to hold the fixing member in the required position relative to the vehicle roof to receive a load carrier.

Amendment dated November 4, 2010

(Currently Amended) A method of attaching a load carrier fixing member to a 14. vehicle, the method comprising applying adhesive to at least one of a roof of the vehicle roof and/or or said fixing member, and attaching said fixing member to the vehicle, the surface for adhering to the vehicle comprises at least one undercut and/or dovetail.

15. (Currently Amended) A method as claimed in claim 14, wherein the load carrier fixing member is a roof rail.

- 16. (Original) A method as claimed in claims 14, wherein the load carrier fixing member is a trim finisher.
- 17. (Withdrawn) A kit for fitting a load carrier fixing to a vehicle, the kit comprising a fixing member as defined in claim 1, and adhesive.
- 18. (Withdrawn) A fixing member for a vehicle load carrier attachment comprising an adhesive receiving portion and a load carrier fixing portion, wherein the load carrier fixing portion is operable to receive a fixing element of the vehicle load carrier attachment.
- 19. (Withdrawn) A fixing member as claimed in claim 18, wherein the adhesive receiving portion incorporates at least one recess adapted to receive adhesive.
- 20. (Withdrawn) A fixing member as claimed in claim 18, wherein the adhesive receiving portion is a locating portion having roof engaging projections, which are operable to locate the locating portion relative to a roof recess.

Application No. 10/584,397 Docket No.: 31229-232408

Amendment dated November 4, 2010

(Withdrawn) A fixing member as claimed in claim 18, wherein a portion of said 21. fixing member is adapted to be hooked under a part of the vehicle roof.

22. (Withdrawn) A method of securing a vehicle load carrier to a vehicle roof using

adhesive and mechanical attachment to the vehicle roof.

(Previously Presented) A method as claimed in claim 1, wherein a portion of said 23.

fixing member is adapted to be hooked under a part of the vehicle roof.

5